


1.Upload the modded BIOS/EFI to your datastore:



2.Download the [vmname].vmx from the datastore and add the line(s):


a) In the case of BIOS:

- bios440.filename = "MODDED_BIOS_NAME.ROM"

The screenshot shows a '7x86Pro-BIOS.vmx - Notepad' window. The window title is '7x86Pro-BIOS.vmx - Notepad'. The menu bar includes 'File', 'Edit', 'Format', 'View', and 'Help'. The main content area contains the following configuration settings:
scsi0.sasWWID = "50 05 05 62 da 31 94 80"
ethernet0.generatedAddress = "00:0c:29:18:b9:ff"
ethernet0.generatedAddressOffset = "0"
vmci0.id = "-1608992257"
monitor.phys_bits_used = "43"
vmotion.checkpointFBSIZE = "16777216"
vmotion.checkpointSVGAPrimarySize = "16777216"
cleanShutdown = "TRUE"
softPowerOff = "TRUE"
usb:0.present = "TRUE"
usb:0.deviceType = "hid"
usb:0.port = "0"
usb:0.parent = "-1"
usb:1.speed = "2"
usb:1.present = "TRUE"
usb:1.deviceType = "hub"
usb:1.port = "1"
usb:1.parent = "-1"
svga.guestBackedPrimaryAware = "TRUE"
bios440.filename = "BIOS.440_SLIC.ROM"

b) In the case of EFI:

- firmware = "efi" (if not already present)
- efi64.filename = "MODDED_EFI_NAME.ROM"



```
7x64Pro-EFI.vmx - Notepad
File Edit Format View Help
svga.present = "TRUE"
pciBridge4.present = "TRUE"
pciBridge4.virtualDev = "pcieRootPort"
pciBridge4.functions = "8"
pciBridge5.present = "TRUE"
pciBridge5.virtualDev = "pcieRootPort"
pciBridge5.functions = "8"
pciBridge6.present = "TRUE"
pciBridge6.virtualDev = "pcieRootPort"
pciBridge6.functions = "8"
pciBridge7.present = "TRUE"
pciBridge7.virtualDev = "pcieRootPort"
pciBridge7.functions = "8"
vmci0.present = "TRUE"
hpet0.present = "TRUE"
floppy0.present = "FALSE"
memSize = "2048"
bios.bootRetry.delay = "10"
firmware = "efi"
efi64.filename = "EFI64_SLIC.ROM"
```

- Save and upload back to the datastore.

3. Start the vm and install the certificate and key:


- save the cert to C:\
- slmgr.vbs /ilc C:\ DELL-DD981F15.XRM-MS
- slmgr.vbs /ipk *****_*****_*****_*****_*****

4. Check activation status:


a) XP Activation Status (oobe/msoobe /a):



b) BIOS/SLIC Activation Status:



c) EFI/SLIC Activation Status:



MSDM-SLIC-CERT-KEY Dumper - v0.6 - By Alphawaves

SLIC TABLE

Software Licensing Description Table:

```

53 4C 49 43 76 01 00 00 01 49 44 45 4C 4C 20 20 SLICv... IDELL
50 45 5F 53 43 33 20 20 09 20 07 01 41 4D 49 20 PE_SC3 . . .AMI
13 00 01 00 00 00 00 00 9C 00 00 00 06 02 00 00 ..... .
00 24 00 00 52 53 41 31 00 04 00 00 01 00 01 00 .$.RSA1. ....
7F F6 C1 05 BE 5C 57 63 A5 8A 68 F3 6E 8F 06 FA ..... \Wc..h.n. ....
AF B4 9F 68 82 23 EC 50 40 5A 73 7F EC E4 07 CB ..h.#.PCZs. ....
DC 25 1A 9C E3 E3 66 11 E0 A5 98 06 C5 80 0A FA .%....f. ....
42 93 86 98 E7 D5 1B D4 D7 3A A4 0B EE E2 7D BE B. .... :. .>.
5F 5B 15 0C AB D0 21 DE BF E9 B5 6E A4 57 B9 8C -[. . . ? . . .n.W. ....
0C D2 BA 3A 69 30 76 94 71 A2 64 D7 4C D8 85 BF . . . i0v.q.d.L. ....
DF A5 6A C8 DC 45 D5 4D 8C B8 8C 05 2F FC 2E 23 .j..E.M. .... / .#.
C4 29 C5 6F 3F 29 6C 6D 57 79 0E B6 75 ED 21 95 .>.o?>lmWy..u.!.
01 00 00 00 B6 00 00 00 00 00 02 00 44 45 4C 4C . . . . . . .DELL
20 20 50 45 5F 53 43 33 20 20 57 49 4E 44 4F 57 PE_SC3 WINDOW
53 20 06 00 02 00 00 00 00 00 00 00 00 00 00 00 S. .... .
00 00 00 00 00 00 38 CC C8 2C C1 28 84 A5 4E BE . . . . . . .8. .... <.N. ....
7E B5 CE 6C 3C 3D 2E 62 DB C8 23 44 D7 20 15 6B ~.1<=.b..#D..k
E8 DE 28 C2 60 6F E7 0E 84 3E 91 31 F9 35 12 F5 .<.o. .>.1.5. ....
56 97 34 BA 26 1C 4B 00 EB A9 29 16 B5 FF BF 37 0.4.&.K. .... >....7
EB 68 34 53 E6 17 B5 29 DF B1 70 BC 57 D7 11 33 .h4S. .... >..p.W..3
10 52 64 39 94 88 80 01 F8 5C CA E2 F1 0F 58 AB .Rd9. .... \. . .X.
5D 95 D1 BB CF 4E E0 EA C3 0A FD 97 D1 1E A3 14 1. . .N. .... .
B7 8C 84 4A AC F2 7A CB F0 C6 B8 3B 8D 35 82 99 . . .J..z.... ;.5..
BF 7A 46 9D 76 52 .zF.vR

```

Signature : "SLIC"
Length : 0x176 <374>
Revision : 0x1 <1>
Checksum : 0x49 <73>
SLIC OA : 2.6
OEM ID : "DELL "
OEM Table ID : "PE_SC3 "
OEM Revision : 0x1072009 <17244169>
Creator ID : "AMI "
Creator Revision : 0x10013 <65555>
OEM Public Key Structure
Length : 0x9C <156>
Reserved : 0x0 <0>
Algorithm : 0x2400 <9216>

5.Other Info:

You can find OEM keys in the XP/Vista/Windows 7/Windows Server Sub-Forums. Certs and SLICS can be found in the BIOS Mods Sub-Forum.